



TYPHOON-XV

Specifications

HIGHBAY LED LIGHT

THB150-01-50-45

LED LIGHTING FOR HANGARS, WAREHOUSE, DISTRIBUTION CENTERS

SAVING 50 – 90% ENERGY COST

LONG LIFE LED 100,000 – 250,000 HOURS (TM-21)

The New LowBay and HighBay is designed to deliver much higher efficiency LED lighting Ideal for tall ceiling areas facilities. Ideal for HANGARS, Distribution Centers, Warehousing, Refrigerated and Freezer Warehouses, Manufacturing and Box Stores. The new LED lighting is perfect for ceilings 16' up to 100'.

Simple On/Off or Fully programmable WIRELESS system

c(UL)us Pending, CE Pending, Patent Pending

NEW LED SMART LUMINAIRES FOR FEDERAL, STATE, MUNICIPAL:

- DEPARTMENT OF DEFENSE
- DEPARTMENT OF THE ARMY
- DEPARTMENT OF THE AIR FORCE
- DEPARTMENT OF THE NAVY
- UNITED STATES MARINES
- UNITED STATES COAST GUARD
- DEPARTMENT OF VETERANS AFFAIRS



LOW PROFILE
24.5" H x 16" Dia.
High Bay

INSTALLATION AND OPERATION:

Automatically adjusts to input line voltage (100-300VAC)

Long Life (100,000 – 250,000 Hours) TM21-10

LM79, LM80, DLC pending, UL Pending

Ten-Year Limited Warranty

ENERGY DATA:

One LED unit = 150 Watts full power 25,000 lumens, 165 lm/w

LED Module Designed for Efficient Thermal Management with Reflectors and Lens

Direct DC Power Input on request (Solar Arrays or other DC Sources)

10% better efficiency with direct DC power

ORDERING INFORMATION

For Example: THB150-01-50-45

Product Family	LED Qty.	LED Color	Qty./ Reflector	Configuration	Bluetooth	Sensors	Power	CRI
THB150	01	50	45					70
150 Watt	01=one	40=4000K 50=5000K	45=45° 90=90° 120=120° PC=45° PS=PC Small	0=Area 1=Aisle	SM=BT	OC DL	0=100-300V 2=36vdc	70 80

Wireless Programmable Daylight and Occupancy Controls (call for quote)

Customizable Modular Designs for any application (call for quote)

Specification THB150-01-50-45

ASSEMBLED
IN USA



Thrive Energy, LLC, 5435 Balboa Blvd., Suite 105, Encino, CA 91316 USA, P: 831-234-3193

Copyright 2016 Thrive Energy, LLC All Rights Reserved



TYPHOON-XV

Specifications

HIGHBAY LED LIGHT

THB150-01-50-45

