



# TYPHOON-X

# Specifications HIGHBAY LED LIGHT THB100-01-50-45

## LED LIGHTING FOR HANGARS, WAREHOUSE, DISTRIBUTION CENTERS

SAVING 50 – 90% ENERGY COST

LONG LIFE LED 100,000 – 250,000 HOURS (TM-21)

The New LowBay and HighBay is designed to deliver much higher efficiency LED lighting Ideal for tall ceiling areas facilities. Ideal for HANGARS, Distribution Centers, Warehousing, Refrigerated and Freezer Warehouses, Manufacturing and Box Stores. The new LED lighting is perfect for ceilings 16' up to 100'.

Simple On/Off or Fully programmable WIRELESS system

c(UL)us Pending, CE Pending, Patent Pending

## NEW LED SMART LUMINAIRES FOR FEDERAL, STATE, MUNICIPAL:

- DEPARTMENT OF DEFENSE
- DEPARTMENT OF THE ARMY
- DEPARTMENT OF THE AIR FORCE
- DEPARTMENT OF THE NAVY
- UNITED STATES MARINES
- UNITED STATES COAST GUARD
- DEPARTMENT OF VETERANS AFFAIRS



LOW PROFILE  
24.5”H x 16” Dia.  
High Bay

### INSTALLATION AND OPERATION:

Automatically adjusts to input line voltage (100-300VAC)

Long Life (100,000 – 250,000 Hours) TM21-10

LM79, LM80, DLC pending, UL Pending

Ten-Year Limited Warranty

### ENERGY DATA:

One LED unit = 100 Watts full power 18,000 lumens, 180 lm/w

LED Module Designed for Efficient Thermal Management with Reflectors and Lens

## Direct DC Power Input on request (Solar Arrays or other DC Sources)

10% better efficiency with direct DC power

### ORDERING INFORMATION

For Example: THB100-01-50-45

| Product Family | LED Qty. | LED Color            | Qty./ Reflector                                       | Configuration     | Bluetooth | Sensors  | Power                 | CRI      |
|----------------|----------|----------------------|---|-------------------|-----------|----------|-----------------------|----------|
| THB100         | 01       | 50                   | 45  |                   |           |          |                       | 70       |
| 100 Watt       | 01=one   | 40=4000K<br>50=5000K | 45=45°<br>90=90°<br>120=120°<br>PC=45°<br>PS=PC Small | 0=Area<br>1=Aisle | SM=BT     | OC<br>DL | 0=100-300V<br>2=36vdc | 70<br>80 |

Wireless Programmable Daylight and Occupancy Controls (call for quote)

Customizable Modular Designs for any application (call for quote)

Specification THB100-01-50-45

ASSEMBLED  
IN USA



Thrive Energy, LLC, 5435 Balboa Blvd., Suite 105, Encino, CA 91316 USA, P: 831-234-3193

Copyright 2016 Thrive Energy, LLC All Rights Reserved



# TYPHOON-X

# Specifications

## HIGHBAY LED LIGHT

### THB100-01-50-45

